



ITEM: 105E	
POLYIMIDE FILM TAPE Anti static	
ADHESIVE BASE: SILICONE ADHESIVE	
Total thickness:	60±2 μ
Backing thickness:	27 μ
Adhesive thickness:	35 µ
Elongation:	52%
Tensile:	31 LB/in
Breakdown (ASTM D149):	6.4 k.volts/mil(max)
Volume Resistance (ASTM D257):	1.4*10 *6 Μ Ω
Tack :	6↑ ball/No. JIS-Z0237
Solvent residual:	1.5↓ %
Solvent resistance:	GOOD
Adhesion:	0.5↑ kg/inch PSTC-1
Cohesion force:	24↑ hrs./25mmx20mmx1Kg
Weather resistance:	GOOD
Temp. range:	-10-290°C 5min

TECHNICAL DATA

- 1. Breakdown: 100-150 KV
- 2. Release force: 400 \downarrow gf/inch ASTM-D1000
- 3. Color: Amber
- 4. UL510

REMARKS:

The technical data is based on the reliable experiment carried by the company. Which however does not guarantee those properties and characteristics that arespecified completely therein your purpose and condition to use this product upon your own responsibility.

www.magnifi-cent.com

1010 Miramar Tower 132 Nathan rd. Kowloon Hong Kong Grand pitterson 132 high way New Jersy USA